### (12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

#### (19) World Intellectual Property Organization International Bureau



# 

# (43) International Publication Date 5 February 2004 (05.02.2004)

#### **PCT**

# (10) International Publication Number WO 2004/012438 A2

(51) International Patent Classification7:

H04N

(21) International Application Number:

PCT/US2003/024001

(22) International Filing Date:

31 July 2003 (31.07.2003)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data: 60/399,865

31 July 2002 (31.07.2002) US

(71) Applicant (for all designated States except US): THOM-SON LICENSING S.A. [FR/FR]; 46, Quai A. Le Gallo, F-92648 Boulogne Cedex (FR).


(72) Inventors; and

(75) Inventors/Applicants (for US only): GEORGE, John, Barrett [US/US]; 11408 Lakeshore Drive, East, Carmel, IN 46033-4410 (US). BURNETT, Angela, Renee [US/US]; 6821 Bretton Wood Drive, Indianapolis, IN 46268 (US).

- (74) Agents: TRIPOLI, Joseph, S. et al.; Thomson Licensing Inc., 2 Independence Way, Suite 200, P.O. Box 5312, Princeton, NJ 08543-5312 (US).
- (81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO,

[Continued on next page]

### (54) Title: CENTER CONVERGENCE OPTIMIZATION IN A PROJECTION DISPLAY APPARATUS



(57) Abstract: Progressive rounding error and convergence error encountered due to multiple use of a center correction adjustment (820) of an image of a video projection display is reduced by calculating a 3 x 3 matrix (770) for a moved color signal where the non center matrix values represent the difference between the initially measured sensor values (Si1,...,Si8) stored at initial alignment (720), and stored most recently measured sensor values (Sp1,...,Sp8). The matrix center value (860) is the sum of the averaged values calculated from the edge center errors, the stored sum of previous moves (MS) and the current move (CP). Rerun of the sensor finding routine (745) resets the stored move sum to zero.



## WO 2004/012438 A2



SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

without international search report and to be republished upon receipt of that report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.